AMENDMENTS

In the Claims

1.   **(Currently Amended)** A network device comprising:
a duplicate packet map (DPM)[[.]]:
a DPM bank, wherein
        said DPM bank comprises said DPM; and
a plurality of DPMs, wherein
        said DPMs comprise said DPM.

2.   (Original) The network device of claim 1, wherein said DPM comprises:
a plurality of DPM fields.

3.   (Original) The network device of claim 2, wherein
said DPM is configured to receive a packet summary value (PSV).

4.   (Original) The network device of claim 3, wherein said DPM is implemented as a
Bloom filter.

5.   (Original) The network device of claim 3, wherein
a one of said DPM fields corresponds to said PSV.

6.   (Original) The network device of claim 3, wherein
each of said DPM fields corresponds to a bit in said PSV.

7.   (Original) The network device of claim 3, wherein
each of said DPM fields is configured to compare a value of a corresponding bit of said
        PSV with a value stored in said each of said DPM fields to generate an output,
        and
a value of each of said outputs indicates whether said value of said corresponding bit of
        said PSV matches said value stored in said each of said DPM fields.

8.   (Original) The network device of claim 3, wherein

each of said DPM fields is configured to be addressed using said PSV, and

a value stored in a one of said DPM fields corresponding to a value of said PSV indicates

whether said packet is said duplicate packet.

9.   (Original) The network device of claim 1, further comprising:

a packet summary value (PSV) generator, wherein

said duplicate packet map (DPM) is coupled to said PSV generator.

10.   (Original) The network device of claim 9, wherein

said PSV generator is configured to generate a PSV based on a packet received by said

PSV generator, and

said DPM is configured to receive said PSV.

11.   (Original) The network device of claim 9, wherein said DPM comprises:

a plurality of DPM fields.

12.   (Original) The network device of claim 11, wherein

a one of said DPM fields corresponds to said PSV.

13.   (Original) The network device of claim 11, wherein

each of said DPM fields corresponds to a bit in said PSV.

14.   (Original) The network device of claim 12, wherein said DPM is implemented as

a Bloom filter.

15.   **(Cancelled)**

16.   **(Cancelled)**

17.   **(Currently Amended)** The network device of claim ~~16~~ 1, wherein

each of said DPMs is implemented as a Bloom filter.

18.   **(Currently Amended)** The network device of claim ~~16~~ 1, wherein

a first one of said DPMs is designated as a current DPM, and

a second one of said DPMs is designated as a previous DPM.

19.   **(Currently Amended)** The network device of claim ~~16~~ 1, wherein said DPM

bank further comprises:

a DPM addressing unit coupled to said DPMs;

a selection unit coupled to said DPMs; and

a DPM control unit, coupled to control said DPM addressing unit, said DPMs and said

        selection unit.

20.   (Original) The network device of claim 19, wherein

said DPM control unit is configured to select a first one of said DPMs as a current DPM

        and a second one of said DPMs as a previous DPM.

21.   (Original) The network device of claim 20, wherein

said DPM control unit is configured to cause said DPM addressing unit to provide said

        PSV to said current DPM and said previous DPM; and

said DPM control unit is configured to cause said selection unit to select said current

        DPM and said previous DPM.

22.   (Original) The network device of claim 20, wherein

said DPM control unit is configured to select said previous DPM as an inactive DPM and

        to clear said inactive DPM.

23.   **(Currently Amended)** The network device of claim ~~15~~ 1, further comprising:

a packet summary value (PSV) generator, wherein

        said duplicate packet map (DPM) is coupled to said PSV generator.

24.   (Original) The network device of claim 23, wherein said DPM bank further comprises:

     a DPM addressing unit coupled between said PSV generator and said DPMs; and

     a selection unit coupled to said DPMs.

25.   (Original) The network device of claim 24, wherein said DPM bank further comprises:

     a DPM control unit, coupled to control said DPM addressing unit, said DPMs and said selection unit.

26.   (Original) The network device of claim 25, wherein

said selection unit is configured to generate a hit signal, and

said hit signal indicates that bit values of said PSV match bit values stored in corresponding locations in a one of said DPMs.

27.   (Original) The network device of claim 9, wherein

said PSV generator is configured to generate a PSV based on a packet received by said PSV generator, and

said DPM is configured to receive said PSV.

28.   (Original) The network device of claim 27, wherein

said DPM is further configured to indicate that said PSV matches a PSV stored in said DPM.

29.   (Original) The network device of claim 28, wherein said PSV generator is configured to generate said PSV using a cyclic redundancy check computation.

30.   (Original) The network device of claim 9, further comprising:

a packet processing unit, said packet processing unit comprising said PSV generator.

31.   (Original) The network device of claim 30, further comprising:

a DPM bank, wherein

> said DPM bank comprises said DPM,
>
> said DPM bank is configured to generate a hit signal, and
>
> said DPM bank is coupled to receive said PSV from said PSV generator and to
>> provide said hit signal to said packet processing unit.

32.   (Original) The network device of claim 31, wherein

said hit signal indicates that a value of said PSV matches a value stored in a one of said
> DPMs.

33.   (Original) The network device of claim 31, wherein

said hit signal indicates that bit values of said PSV match bit values stored in
> corresponding locations in a one of said DPMs.

34.   (Original) The network device of claim 31, wherein

said packet processing unit is configured to process said packet using said hit signal.

35.   (Original) The network device of claim 31, wherein

said processing includes causing said packet processing unit to drop said packet based on
> said hit signal.

36.   **(Currently Amended)** A method ~~for determining if a packet is a duplicate~~
~~packet,~~ comprising:

> **determining if a packet is a duplicate packet, wherein**
>> **the determining comprises**
>>> determining if a field of a duplicate packet map (DPM) indicates said
>>>> packet is ~~said~~ <u>a</u> duplicate packet, wherein
>>> said determination is made using <u>**a DPM, a DPM bank, a plurality of**</u>
>>>> <u>**DPMs, and**</u> a packet summary value (PSV) corresponding to said
>>>> packet.

PATENT

37.   (Original) The method of claim 36, further comprising:

indicating said packet is said duplicate packet, if said determination determines said

packet is said duplicate packet.

38.   (Original) The method of claim 37, further comprising:

dropping said packet, if said packet is said duplicate packet.

39.   **(Currently Amended)** The method of claim 37, wherein said determining

comprises:

~~39~~ <u>comparing</u> said PSV to said DPM.

40.   (Original) The method of claim 39, wherein

said determination is made by comparing a bit of said PSV with a bit stored in said field

of said DPM, and

said indicating is performed if said bit of said PSV matches said bit stored in said field of

said DPM.

41.   (Original) The method of claim 40, further comprising:

setting said bit stored in said field of said DPM to a value of said bit of said PSV.

42.   (Original) The method of claim 37, wherein said determining comprises:

selecting said field of said DPM based on said PSV.

43.   (Original) The method of claim 42, wherein

said determination is made by selecting said field of said DPM based on a value of said

PSV, and

said indicating is performed if a value stored in said field of said DPM indicates that said

packet is said duplicate packet.

44.   (Original) The method of claim 43, further comprising:

setting said value stored in said field of said DPM, if said packet is not said duplicate

packet.

-7-   Application No.: 10/626,792

45.   (Original) The method of claim 44, further comprising:

generating said PSV by generating a cyclic redundancy check value based on information

        in said packet.

46.   (Original) The method of claim 37, wherein

said DPM is a one of a plurality of DPMs.

47.   (Original) The method of claim 46, further comprising:

selecting a first DPM of said DPMs as a previous DPM; and

selecting a second DPM of said DPMs as a current DPM.

48.   (Original) The method of claim 47, further comprising:

determining if a field of said previous DPM indicates said packet is said duplicate packet,

        using said PSV; and

determining if a field of said current DPM indicates said packet is said duplicate packet,

        using said PSV.

49.   (Original) The method of claim 48, further comprising:

indicating said packet is not said duplicate packet, if said field of said previous DPM

        indicates said packet is not said duplicate packet and said field of said current

        DPM indicates said packet is not said duplicate packet, and

indicating said packet is said duplicate packet, otherwise.

50.   (Original) The method of claim 47, further comprising:

selecting said previous DPM as an inactive DPM;

selecting said current DPM as said previous DPM; and

selecting another DPM of said DPMs as said current DPM.

51.   (Original) The method of claim 50, further comprising:

clearing said inactive DPM prior to said inactive DPM being selected as said current

        DPM.

Application No.: 10/626,792

52.   (Original) The method of claim 50, wherein

said selecting said previous DPM as said inactive DPM, said selecting said current DPM
        as said previous DPM, and said selecting said another DPM of said DPMs as said
        current DPM are performed periodically.

53.   (Original) The method of claim 52, wherein

a period of said performing periodically is such that said period is greater than an
        expected differential between duplicate packet arrivals and said period is less than
        a time between packet retransmissions.

54.   (Original) The method of claim 52, wherein

a period of said performing periodically is configured to allow said inactive DPM to be
        cleared prior to said inactive DPM being selected as said current DPM.

55.   **(Currently Amended)** A network device comprising:

a processor;

computer readable medium coupled to said processor; and

computer code, encoded in said computer readable medium, for determining if a packet is
        a duplicate packet and configured to cause said processor to:
            determine if a field of a duplicate packet map (DPM) indicates said packet is ~~said~~
                <u>a</u> duplicate packet, wherein
                    said computer code configured to cause said processor to determine uses <u>a</u>
                        <u>**DPM, a DPM bank, a plurality of DPMs, and**</u> a packet summary
                        value (PSV) corresponding to said packet~~,~~.

56.   (Original) The network device of claim 55, wherein said computer code is further
configured to cause said processor to:
        indicate said packet is said duplicate packet, if said computer code configured to cause
            said processor to determine determines said packet is said duplicate packet.

57.   (Original) The network device of claim 56, wherein said computer code is further
configured to cause said processor to:

compare said PSV to said DPM.

58.   (Original) The network device of claim 56, wherein said computer code is further configured to cause said processor to:

select said field of said DPM based on said PSV.

59.   (Original) The network device of claim 58, wherein said computer code is further configured to cause said processor to:

generate said PSV by virtue of being configured to generate a cyclic redundancy check
value based on information in said packet.

60.   (Original) The network device of claim 55, wherein
said DPM is a one of a plurality of DPMs.

61.   (Original) The network device of claim 60, wherein said computer code is further configured to cause said processor to:

select a first DPM of said DPMs as a previous DPM; and
select a second DPM of said DPMs as a current DPM.

62.   (Original) The network device of claim 61, wherein said computer code is further configured to cause said processor to:

determine if a field of said previous DPM indicates said packet is said duplicate packet,
using said PSV; and
determine if a field of said current DPM indicates said packet is said duplicate packet,
using said PSV.

63.   (Original) The network device of claim 62, wherein said computer code is further configured to cause said processor to:

indicate said packet is not said duplicate packet, if said field of said previous DPM
indicates said packet is not said duplicate packet and said field of said current
DPM indicates said packet is not said duplicate packet, and
indicate said packet is said duplicate packet, otherwise.

64.   (Original) The network device of claim 61, wherein said computer code is further configured to cause said processor to:

select said previous DPM as an inactive DPM;

select said current DPM as said previous DPM; and

select another DPM of said DPMs as said current DPM.

65.   (Original) The network device of claim 64, wherein

said computer code further configured to cause said processor to select said previous

DPM as said inactive DPM, said computer code further configured to cause said

processor to select said current DPM as said previous DPM, and said computer

code further configured to cause said processor to select said another DPM of said

DPMs as said current DPM are further configured to be performed periodically.

66.   (Original) The network device of claim 65, wherein

a period of said performing periodically is such that said period is greater than an

expected differential between duplicate packet arrivals and said period is less than

a time between packet retransmissions.

67.   (Original) The network device of claim 65, wherein

a period of said performing periodically is configured to allow said inactive DPM to be

cleared prior to said inactive DPM being selected as said current DPM.

68.   **(Currently Amended)** A computer program product for determining if a packet is a duplicate packet, comprising:

a first set of instructions, executable on a computer system, configured to determine if a

field of a duplicate packet map (DPM) indicates ~~said~~ a packet is said duplicate

packet, wherein

said first set of instructions makes said determination using **a DPM, a DPM**

bank, a plurality of DPMs, and a packet summary value (PSV)

corresponding to said packet; and

computer readable **storage** media, wherein said computer program product is encoded in

said computer readable **storage** media.

Application No.: 10/626,792

69.　(Original)　The computer program product of claim 68, further comprising:
a second set of instructions, executable on said computer system, configured to indicate
　　　said packet is said duplicate packet, if said computer code configured to cause
　　　said processor to determine determines said packet is said duplicate packet.

70.　(Original)　The computer program product of claim 69, further comprising:
a third set of instructions, executable on said computer system, configured to compare
　　　said PSV to said DPM.

71.　(Original)　The computer program product of claim 69, further comprising:
a third set of instructions, executable on said computer system, configured to select said
　　　field of said DPM based on said PSV.

72.　(Original)　The computer program product of claim 71, further comprising:
a fourth set of instructions, executable on said computer system, configured to generate
　　　said PSV by virtue of being configured to generate a cyclic redundancy check
　　　value based on information in said packet.

73.　(Original)　The computer program product of claim 68, wherein
said DPM is a one of a plurality of DPMs.

74.　(Original)　The computer program product of claim 73, further comprising:
a second set of instructions, executable on said computer system, configured to select a
　　　first DPM of said DPMs as a previous DPM; and
a third set of instructions, executable on said computer system, configured to select a
　　　second DPM of said DPMs as a current DPM.

75.   (Original) The computer program product of claim 74, further comprising:

a fourth set of instructions, executable on said computer system, configured to determine
        if a field of said previous DPM indicates said packet is said duplicate packet,
        using said PSV; and

a fifth set of instructions, executable on said computer system, configured to determine if
        a field of said current DPM indicates said packet is said duplicate packet, using
        said PSV.

76.   (Original) The computer program product of claim 75, further comprising:

a sixth set of instructions, executable on said computer system, configured to indicate
        said packet is not said duplicate packet, if said field of said previous DPM
        indicates said packet is not said duplicate packet and said field of said current
        DPM indicates said packet is not said duplicate packet, and

a seventh set of instructions, executable on said computer system, configured to indicate
        said packet is said duplicate packet, otherwise.

77.   (Original) The computer program product of claim 74, further comprising:

a fourth set of instructions, executable on said computer system, configured to select said
        previous DPM as an inactive DPM;

a fifth set of instructions, executable on said computer system, configured to select said
        current DPM as said previous DPM; and

a sixth set of instructions, executable on said computer system, configured to select
        another DPM of said DPMs as said current DPM.

78.   (Original) The computer program product of claim 77, wherein

said fourth, said fifth, and said sixth set of instructions are performed periodically.

79.   **(Currently Amended)** The computer program product of claim ~~68~~ 78, wherein

a period of said performing periodically is such that said period is greater than an
        expected differential between duplicate packet arrivals and said period is less than
        a time between packet retransmissions.

80.   (Currently Amended) The computer program product of claim 68 78, wherein a period of said performing periodically is configured to allow said inactive DPM to be cleared prior to said inactive DPM being selected as said current DPM.

81.   (Currently Amended) An apparatus method for determining if a packet is a duplicate packet, comprising:

means for determining if a field of a duplicate packet map (DPM) indicates said a packet is said a duplicate packet, wherein

said means for determining uses a DPM, a DPM bank, a plurality of DPMs, and a packet summary value (PSV) corresponding to said packet[[.]];

means for indicating said packet is said duplicate packet, said means for indicating configured to indicate said packet is said duplicate packet if said means for determining determines said packet is said duplicate packet; and

means for selecting said field of said DPM based on said PSV.

82.   (Cancelled)

83.   (Currently Amended) The apparatus of claim 82 81, wherein said determining comprises:

means for comparing said PSV to said DPM.

84.   (Cancelled)

85.   (Currently Amended) The apparatus of claim 84 81, further comprising:

means for generating said PSV comprising a means for generating a cyclic redundancy check value based on information in said packet.

86.   (Currently Amended) The apparatus of claim 82 81, wherein said DPM is a one of a plurality of DPMs.

87.   (Original) The apparatus of claim 86, further comprising:

means for selecting a first DPM of said DPMs as a previous DPM; and

means for selecting a second DPM of said DPMs as a current DPM.

88.   (Original) The apparatus of claim 87, further comprising:

means for determining if a field of said previous DPM indicates said packet is said
        duplicate packet, using said PSV; and

means for determining if a field of said current DPM indicates said packet is said
        duplicate packet, using said PSV.

89.   (Original) The apparatus of claim 88, further comprising:

means for indicating said packet is not said duplicate packet, if said field of said previous
        DPM indicates said packet is not said duplicate packet and said field of said
        current DPM indicates said packet is not said duplicate packet, and

means for indicating said packet is said duplicate packet, otherwise.

90.   (Original) The apparatus of claim 87, further comprising:

means for selecting said previous DPM as an inactive DPM;

means for selecting said current DPM as said previous DPM; and

means for selecting another DPM of said DPMs as said current DPM.

91.   (Original) The apparatus of claim 90, further comprising:

means for clearing said inactive DPM prior to said inactive DPM being selected as said
        current DPM.

92.   (Original) The apparatus of claim 90, wherein

said means for selecting said previous DPM as said inactive DPM, said means for
        selecting said current DPM as said previous DPM, and said means for selecting
        said another DPM of said DPMs as said current DPM perform their respective
        selections periodically.